


DELK

5.8 GHZ PARABOLIC ANTENNAS

- D5827
- D5830
- D5832

DESCRIPTION

These 5.8 GHz solid parabolic dishes include a tilt mount for ease of installation. The solid aluminum provides a high front-back ratio (30 dB or more). These solid dishes are also available in 2.4 GHz and 3.4 GHz frequency bands.

APPLICATION

- Point-to-Point networks over longer distances.
- Client site for multi-point network

SPECIFICATIONS

Electrical

MODEL	D5827	D5830	D5832
FREQUENCY	5.7—5.85 GHz	5.7—5.85 GHz	5.7—5.85 GHz
GAIN	27.5 dBi	30.0 dBi	32.5 dBi
IMPEDANCE	50 Ohm	50 Ohm	50 Ohm
VSWR	2:1	2:1	2:1
F/B RATIO	30 dB	32 dB	34 dB
POLARIZATION	HORIZONTAL OR VERTICAL	HORIZONTAL OR VERTICAL	HORIZONTAL OR VERTICAL
HPBW "E" PLANE	7.0 DEGREES	5.3 DEGREES	4.0 DEGREES
"H" PLANE	7.0 DEGREES	5.3 DEGREES	4.0 DEGREES
CROSS POL REJECTION	25 dB	25 dB	25 dB
TERMINAL TYPE	N FEMALE	N FEMALE	N FEMALE
MAXIMUM INPUT POWER	20 WATTS	20 WATTS	20 WATTS

Mechanical

MODEL	D5827	D5830	D5832
SIZE	24" DIAMETER X 12" DEPTH	32" DIAMETER X 12" DEPTH	43" DIAMETER X 16" DEPTH
DISH MATERIAL	SOLID ALUMINUM DISH	SOLID ALUMINUM DISH	SOLID ALUMINUM DISH
FEED MATERIAL	ABS PLASTIC	ABS PLASTIC	ABS PLASTIC
WEIGHT	5 LBS (2.38 KG)	8 LBS (3.81 KG)	12.5 LBS (5.95 KG)
MOUNTING	UP TO 2" O.D. MAST	UP TO 2" O.D. MAST	UP TO 2" O.D. MAST

WADE Antenna's ongoing policy of continuing development may result in specification changes to its products.

WADE Antenna Inc.

29 Sharp Road
 Brantford, Ontario, N3T 5L8 Canada
 Tel: 519.756.7157
 Fax: 519.756.5056

(800) 463-1607
sales@wadeantenna.com

www.wadeantenna.com